

Programming (ERIM)

Lecture 8: Anonymous functions and function references

Tommi Tervonen

Econometric Institute, Erasmus School of Economics

Anonymous functions: definition

- Anonymous functions are functions that are not bound to any identifier, i.e. name

- R:

```
(function(x) { x * x })(5)
```

- Matlab:

```
(@(x) x * x)(5)
```

- When calling a named function, the name represents reference to the actual execution code
- Similarly, anonymous functions define references that are often immediately passed somewhere
- Matlab's @ is similar to R's function:

```
f = @(x, y) x + y;  
f(2, 3)
```

- In R, you can see the source code of functions written in R by executing the function without arguments in command-line
- Same in Matlab for functions constructed with @

Using function references

- Function references allows to parameterize methods with functionality that is left free for definition
- This is similar to implementing interfaces in strongly-typed OOP languages

```
apply(m, 1, function(x) {  
    ## do something with each row ##  
})
```

GUI vs console

- Console (execution environment)

- Console (execution environment)
- Good text editor

- Console (execution environment)
- Good text editor
- Unit testing framework

- Console (execution environment)
- Good text editor
- Unit testing framework
- Source control (git)

- Console (execution environment)
- Good text editor
- Unit testing framework
- Source control (git)
- Source repository (github)

- Console (execution environment)
- Good text editor
- Unit testing framework
- Source control (git)
- Source repository (github)
- Build system (GNU Make, Maven)

Tools of the trade

- Console (execution environment)
- Good text editor
- Unit testing framework
- Source control (git)
- Source repository (github)
- Build system (GNU Make, Maven)
- Continuous integration server (Hudson)